

Williamson County, Tennessee Sewage Disposal Management Department	PERMIT FOR CONSTRUCTION OF SUBSURFACE SEWAGE DISPOSAL SYSTEM	1320 West Main St, Ste 411 Franklin, Tennessee 37064 615-790-5751
-- PERMIT VOID 3 YEARS AFTER ISSUE DATE --		
PERMIT NO: SDM-CS-LPP-2026-00026	GIS NO: 146 01006	
PERMIT DATE: 03/24/2026	PROJECT ID: 2082436	

NAME: Doug Manhardt

EMAIL: dougmanhardt64@gmail.com

ADDRESS: 1907 SEDBERRY RD

PHONE: 615-924-2540

SUBDIVISION NAME:	HELTON JAMES T III PROPERTY	LOT NUMBER:	TRACT 2
INSTALLATION:	New	TYPE OF SYSTEM:	LPP
PUMP TANK CAPACITY:	1250 GALLONS	ESTABLISHMENT:	Residential
SEPTIC TANK CAPACITY:	1000 GALLONS	BEDROOMS:	FOUR
SOIL EVAL. BASIS:	Soils typing by Soils Scientist - Extra High Intensity	OVERSIZED TUBS:	
EST. ABSORPTION RATE:	45 MPI	TUB CAPACITY:	
GPD:	600 GALLONS PER DAY	PERMIT ISSUED BY:	KEVIN RALEY
OTHER:			

- SYSTEM, HOUSESITE AND ALL RELATED APPENDAGES ARE TO BE IN ACCORDANCE WITH SITE AND DESIGN PLANS AS SUBMITTED BY TRENT B. SMITH DATED 9-13-22 AND AS APPROVED BY BRIAN CORWIN ON 8-25-23.
- **ENSURE THAT THE SEPTIC AREAS ARE PROPERLY STAKED.**
- A DEPARTMENT APPROVED EFFLUENT FILTER (*NSF STANDARD 46* CERTIFIED AND COMPLIANT WITH *SECTION 37* OF THE DEPARTMENT'S CURRENT *REGULATIONS*) SHALL BE INSTALLED IN THE OUTLET OF THE SEPTIC TANK.
- NO PART OF THE PLATTED SUBSURFACE SEWAGE DISPOSAL SYSTEM AREAS IS TO BE DISTURBED BY COMPACTION, CUTTING, OR FILLING NOR IS ANY PART OF THE AREAS TO BE ENCROACHED UPON BY ANY PART OF THE HOUSE, DRIVEWAYS, OR ANY UNDERGROUND OR OVERHEAD UTILITIES (GAS, WATER, ELECTRIC, ETC.).
- WELL, SPRING, OR CISTERN MUST BE A MINIMUM OF 50 FEET FROM ANY PART OF THE PLATTED SUBSURFACE SEWAGE DISPOSAL SYSTEM AREAS OR SEPTIC / PUMP TANKS.
- WATER, GAS, OR UNDERGROUND ELECTRIC LINES MUST BE A MINIMUM OF 10 FEET FROM ANY PART OF THE PLATTED SUBSURFACE SEWAGE DISPOSAL SYSTEM AREAS OR SEPTIC / PUMP TANKS.
- OVERHEAD UTILITIES MUST BE A MINIMUM OF 25 FEET FROM ANY PART OF THE PLATTED SUBSURFACE SEWAGE DISPOSAL SYSTEM AREAS.
- LATERAL LINES AND SEPTIC / PUMP TANKS MUST BE A MINIMUM OF 20 FEET FROM ANY PROPERTY LINE.
- ANY CUTTING FOR THE PURPOSE OF HOUSE OR DRIVEWAY CONSTRUCTION, GREATER THAN 18 INCHES, MUST BE A MINIMUM OF 25 FEET FROM ANY PART OF THE PLATTED SUBSURFACE SEWAGE DISPOSAL SYSTEM AREAS.
- A CURTAIN DRAIN IS REQUIRED AT A MINIMUM DEPTH OF 36 INCHES AND MUST BE TAKEN TO A POSITIVE OUTLET IN ACCORDANCE WITH THE DESIGN PLANS.
- THIS APPROVAL IS LIMITED TO ONE-4 BEDROOM SINGLE FAMILY DWELLING.
- THE INSTALLER MUST CONTACT WCSDSM PRIOR TO SYSTEM INSTALLATION TO INITIATE THE **PERMIT TO INSTALL** PROCESS.

The recipient of this permit agrees to construct or have constructed the system described above in accordance with the Regulations to Govern On-Site Sewage Disposal Systems of the Williamson County Department of Sewage Disposal Management, as operated under the auspices of the Williamson County Board of Health, and T.C.A. 68-221-401 et. seq. All installers of subsurface sewage disposal systems must hold a valid annual license from the Williamson County Department of Sewage Disposal Management.